

IBM InfoSphere Information Server
Version 11 Release 3

*Importing Metadata by Using the
MicroStrategy Bridge*



IBM InfoSphere Information Server
Version 11 Release 3

*Importing Metadata by Using the
MicroStrategy Bridge*



Note

Before using this information and the product that it supports, read the information in “Notices and trademarks” on page 23.

Contents

Chapter 1. Importing metadata from business intelligence tools	1
Business intelligence metadata	1
Chapter 2. Importing metadata by using InfoSphere Metadata Asset Manager . . .	3
Chapter 3. MicroStrategy bridge reference	5
Upgrade requirements for users of MicroStrategy bridge	7
Chapter 4. Identity parameters for imported assets	9
Chapter 5. Business intelligence assets	13
Appendix A. Product accessibility . . .	17
Appendix B. Contacting IBM	19
Appendix C. Accessing the product documentation	21
Notices and trademarks	23
Index	29

Chapter 1. Importing metadata from business intelligence tools

You can use bridges to import business intelligence (BI) metadata into the metadata repository of IBM® InfoSphere® Information Server. The imported metadata includes BI reports, BI models, and related implemented data resources such as database tables.

Business intelligence metadata

When you import BI metadata into the metadata repository, you can study the components of BI reports and BI models and how they are related. You can track database tables and columns that the BI reports reference, and the jobs that use the columns.

Business intelligence reporting is the means of publishing, distributing, and reviewing data results and information. Analysts must be able to understand the meaning and authenticity of BI reports, which are generated against data sources such as marts or warehouses. You might need to know when the content that feeds a BI report was last updated, and which InfoSphere DataStage® and QualityStage® jobs or other processes were sequenced during the update. Lineage and analysis reports in InfoSphere Information Governance Catalog can display the complete data flows that transform and populate the source data that underlies the BI reports, thus satisfying requirements for data governance and data trust.

For a full list of supported BI bridges, see the technote *List of supported bridges for InfoSphere Information Server Version 11.3*: <http://www.ibm.com/support/docview.wss?&uid=swg27042029>. Not all BI bridges import BI reports.

BI reports are the report templates that are created within BI reporting tools such as the following:

- IBM Cognos® Report Studio or Query Studio
- SAP BusinessObjects Desktop Intelligence, Web Intelligence, or Crystal Reports
- Oracle Business Intelligence Report Publisher
- MicroStrategy
- Microsoft SQL Server Report Builder and Report Designer

BI reports include BI queries and query members, which source and aggregate the information to display from BI models. BI models are created within modeling tools such as Cognos Framework Manager and BusinessObjects Designer.

In InfoSphere Information Governance Catalog, you can assign stewards and glossary terms to business intelligence reports, and edit the business names and descriptions of the reports.

For best results when you import BI metadata, familiarize yourself with the following concepts and functionality:

To answer this question	Read this
How do I ensure that my imports are efficient and successful?	Importing and managing assets by using InfoSphere Metadata Asset Manager (http://www.ibm.com/support/knowledgecenter/SSZJPZ_11.3.0/com.ibm.swg.im.iis.mmi.doc/topics/ct_imam_top-level.html)
Which assets are imported and used by suite tools, and how are they organized?	Common metadata assets (http://www.ibm.com/support/knowledgecenter/SSZJPZ_11.3.0/com.ibm.swg.im.iis.metadata.common.doc/topics/ct_common_metadata_assets.html)
Which BI assets are imported and used?	Business intelligence assets
How do I view and report on the relationships between the imported BI metadata and the InfoSphere DataStage and QualityStage jobs that use the database tables and columns that reports are based on?.	Reporting data lineage and business lineage (http://www.ibm.com/support/knowledgecenter/SSZJPZ_11.3.0/com.ibm.swg.im.iis.mdwb.doc/topics/ct_analyzingMetadataRelationships.html)

Chapter 2. Importing metadata by using InfoSphere Metadata Asset Manager

You can import by using a bridge or connector that is on any computer that is designated as a metadata interchange server. You specify connection information and information about the source metadata, and choose to run either an express import or a managed import.

Before you begin

You must have the role of Common Metadata Importer or Common Metadata Administrator.

Ensure that you meet all prerequisites for importing metadata:

- Installing InfoSphere Metadata Asset Manager and bridges (http://www.ibm.com/support/knowledgecenter/SSZJPZ_11.3.0/com.ibm.swg.im.iis.productization.iisinfsv.install.doc/topics/wsisinst_install_imam.html)
- Preparing to use InfoSphere Metadata Asset Manager (http://www.ibm.com/support/knowledgecenter/SSZJPZ_11.3.0/com.ibm.swg.im.iis.mmi.doc/topics/t_first_steps.html)
- Prerequisites for using the MicroStrategy bridge

About this task

You create an import area by running an import. The import area is created whether you run an express import or a managed import.

When you run a managed import, you can closely study the metadata assets in the import. You can preview the effects that the import might have on the repository. You can take time to fix problems in the source metadata, or reimport with other parameters.

An express import saves time when you have high confidence in the contents of your import source. By default, an express import requires that you preview the result of sharing to the metadata repository if repository assets will be deleted as a result of the import. Your administrator can change the defaults to allow automatic sharing in all cases or to require previews in all cases.

Procedure

1. Log in to InfoSphere Metadata Asset Manager by clicking the desktop icon or entering the URL for the services tier computer in your browser. The URL is `https://server:port/ibm/iis/imam/console`. The default port number is 9443 for HTTPS.
2. On the **Import** tab, click **New Import Area**.
3. In the **New Import Area** window, take the following steps:
 - a. Specify a unique name and a description for the import area.
 - b. Select the metadata interchange server from which you want to run the import.
 - c. From the list of bridges and connectors, select **MicroStrategy**.

- d. Click **Next**.
4. For connector imports, and imports with the HDFS bridge, select or create a data connection. You can edit the properties of a selected data connection.
5. Specify import parameters for the MicroStrategy bridge Help for each parameter is displayed when you hover over the value field.
 - a. After you enter connection information for an import from a server, click **Test Connection**.
 - b. For imports from databases and repositories, browse to select the specific assets that you want to import.
 - c. Click **Next**.
6. If required, on the Identity Parameters screen, specify identity parameters for database assets or data models that you are importing. Consult the help for each selected parameter. Click **Next**.
7. Type a description for the import event and specify whether to run an express import or a managed import.
8. Click **Import**. The import area is created. The import runs and status messages are displayed.

Leave the import window open to avoid the possibility that long imports time out.

Results

When the import completes, if you ran a managed import, analyze the imported assets in the **Staged Imports** tab of the import area.

If you ran an express import, take one of the actions that are listed in the following table.

Table 1. Choices after an express import

In this case	Take this action
If the analysis shows problems that you must fix	The Staged Imports tab is displayed. Review the analysis results. If necessary, reimport the staged event.
If your administration settings require a preview	The View Share Preview screen is displayed. Preview the result of sharing the import.
If your administration settings do not require a preview	The assets are shared to the metadata repository. The Shared Imports tab is displayed. You can browse the assets on the Repository Management tab and work with them in other suite tools.

What to do next

If you want to use imported database tables or data file structures in InfoSphere DataStage and QualityStage jobs, you must create table definitions. To create table definitions from the database tables or data file structures, in the Designer client, click **Repository > Metadata sharing > Create table definition from shared table**, and then select the imported asset that you want to create a table definition from.

Chapter 3. MicroStrategy bridge reference

Prerequisites, troubleshooting, and parameter information for the MicroStrategy import bridge.

About this bridge

The MicroStrategy bridge imports business intelligence (BI) models, BI reports, and related implemented data resources such as database tables from MicroStrategy Intelligence Server, versions 7 to 9.

The bridge imports the contents of a single project. The bridge does not import information about database connections or users. The bridge imports MicroStrategy logical tables as BI collections. Derived elements are not supported.

The bridge does not capture the following relationships:

- Between HTML documents and the reports they embed
- Between reports and the intelligent cube they use
- Between reports and direct SQL sources, such as freeform SQL reports

“Prerequisites”

“Troubleshooting”

“Import parameters” on page 6

Prerequisites

Ensure that you meet the following prerequisites before you run the bridge:

- You must install a supported version of MicroStrategy on the same computer that the bridge is installed on. This version of MicroStrategy must be able to open the metadata to be imported.
- MicroStrategy database corruption can prevent the bridge from working correctly. Such corruption is reported in the MicroStrategy log file: C:\Program Files\Common Files\MicroStrategy\Log\DSSErrors.log. MicroStrategy support is aware of this issue and provides a ScanMD program that you can use to clean up these errors. Always run the ScanMD program before using this bridge.
- MicroStrategy automatically creates reports whenever you create a project. The bridge does not differentiate between these reports and the reports that users create. To import only the reports that users create, delete the automatically generated reports from the MicroStrategy project before you run the bridge.

Troubleshooting

To provide information to help the support team reproduce an issue, create a backup of the relational database that MicroStrategy uses to store project metadata:

1. Run the Microsoft ScanMD program.
2. Use the relational database management system utilities to create a database backup.
3. Give the support team the database backup file and the MicroStrategy user name and password for logging in.

Import parameters

The MicroStrategy bridge uses the following import configuration parameters.

Version

Required. Select the version of MicroStrategy that you want to connect to. The default selection, **Auto-detect**, the version that is installed.

Options

- **Auto-detect**
- **9**
- **8.0.0 to 8.1.2**
- **7.5.2**
- **7.5.0**
- **7.0**

Project source

Required. Browse to select the name of the MicroStrategy project source to connect to, or type the name.

A project source is a connection to a repository that is located on a local or remote Intelligence Server. The server holds connectivity to a data warehouse and contains a number of metadata projects that operate on this data warehouse. The list of project sources that are accessible from this computer is stored in the Windows registry.

To connect to a remote Intelligence Server that is not registered on the local computer, create a project source in MicroStrategy that points to the Intelligence Server.

Projects

Required. Browse to select the names of one or more projects that you want to connect to in the selected project source, or type the names.

Login user

Required. Type the user name to connect to the project source. This import bridge is read-only and never affects the contents of the MicroStrategy repository. It is therefore safe to attempt the initial metadata import as Administrator to ensure that the entire repository content is imported without access permission issues. Eventually, the administrator can set up a read-only user. For more details, see the MicroStrategy documentation on permissions and security.

Login password

Type the password to connect to the project source.

Default Language

If you use MicroStrategy version 9, specify the language that you would like to use. Only MicroStrategy version 9 supports multiple languages. English is the default.

Import schema only

Leave this option unselected to import both database and BI report metadata. Both types of metadata are necessary for data lineage.

Table design level

Specify whether you want the bridge to create logical entities from the physical tables.

If you select **Logical and physical**, logical entities and a logical data model are created and imported with the physical tables that implement them. If you accept the default **Physical**, no logical entities are created.

Incremental import

Keep this parameter selected. When you reimport from the same source, the bridge uses cached information to determine which objects did not change since the previous import. Only changed objects are reimported. Using the cached information can increase performance for large imports.

For new imports, or when the cache is deleted or corrupted, the bridge imports all objects from the source regardless of the selection that is specified.

Import joins

You can import joins that are defined in the BI model. By default, joins are not imported.

Import levels

You can import levels and hierarchies. When the option is selected, levels and hierarchies that are defined in the BI model are imported. By default, they are not imported.

Metadata consistency check

Perform a consistency check on the selected metadata before it is imported into the metadata repository. It is possible to save metadata in source tools in ways that cause problems when the assets are imported into the metadata repository or used in other tools. For example, a foreign key might have no connection to a primary key or to an alternate key. In some cases, the metadata might be so semantically inconsistent that the bridge cannot import it.

The metadata consistency check returns warnings and errors in the log file.

Basic check

The default. Performs the minimum consistency checks necessary to validate the metadata, including checking for missing relationships and foreign keys that are not connected to primary or alternate keys.

In some cases, the basic check might be more rigorous than necessary and you can ignore certain errors or warnings.

Detailed check

Performs the basic check plus more advanced semantic checks specific to the type of metadata that is imported. This level can be used when the source tool does not have the ability to validate the metadata.

No check

Use with extreme caution. Selecting this option could result in the import of duplicates or invalid identities and might cause serious problems with your use of suite tools and the metadata repository.

Upgrade requirements for users of MicroStrategy bridge

Users who upgrade to InfoSphere Information Server, Version 9.1, must be aware of the following requirements for importing metadata.

Sharing and reimporting staged imports

The method of identifying and reconciling business intelligence assets changed at InfoSphere Information Server, Version 9.1. If you reimport metadata that was shared you might create duplicate assets or delete existing assets.

To protect the integrity of your imported metadata, the following requirements are enforced at the import area level in InfoSphere Metadata Asset Manager:

- You cannot share staged imports that were created before the upgrade to version 9.1.
- You cannot reimport into the same import area.
- You can create a new import area by copying the settings of the existing area, as described in [Creating an import area from an existing staged import](http://publib.boulder.ibm.com/infocenter/iisinfsv/v9r1/topic/com.ibm.svg.im.iis.mmi.doc/topics/t_copying_staged_import.html). (http://publib.boulder.ibm.com/infocenter/iisinfsv/v9r1/topic/com.ibm.svg.im.iis.mmi.doc/topics/t_copying_staged_import.html).

Important: Before you create a new import area, see the technote [Upgrading BI bridge imports at InfoSphere Information Server, Version 9.1](#). This technote can help you avoid creating duplicate assets or deleting existing assets.

Specifying a value for the Import Levels parameter

In previous versions of the bridge, levels and hierarchies were imported by default. To import levels and hierarchies in version 9.1, you must select **Import levels** on the **Parameters** screen of the import wizard in InfoSphere Metadata Asset Manager.

Chapter 4. Identity parameters for imported assets

You specify values for identity parameters when you import database assets, logical data models, or physical data models. Specifying identity values helps prevent duplicate assets in the metadata repository and ensures that you do not overwrite assets by mistake.

When you use consistent values for identity parameters, suite users can readily identify which assets to use for such tasks as creating jobs, designating stewards, or assigning to terms.

You specify values on the Identity Parameters screen when you import database assets, logical data models, or physical data models by using InfoSphere Metadata Asset Manager.

Database assets

The bridges and connectors that import metadata from remote databases and repositories occasionally provide incomplete or inconsistent information about the host systems and databases that contain the assets that you are importing.

The identity of a database table has the following components:

- Host system name
- Database identity, consisting of database name, DBMS name, and DBMS server instance name
- Database schema name
- Database table name

Thus, host name, database name, database management system (DBMS) name, and DBMS server instance name are critical parts of the identity of the tables and schemas that they contain. If you were to import the same database assets by two different methods, and each method produced a different DBMS name, you could create duplicate assets in the metadata repository. Assets that have technically different identities but have identical content or contain the same child assets are potential duplicates.

To avoid duplicates and to ensure that your database assets are correctly identified, you specify values for identity parameters during the import process. Identity parameters are also valuable when you want the imported assets to be associated with a different host system, database, or DBMS than you imported them from. For example, you might want the assets to be identified with the host system and database that you use for test and production. For the host system, database, and schema parameters you can either type a name or select a host, database, or schema that is already in the metadata repository to associate the imported assets with.

Depending on the bridge or connector that you choose for import, you can specify values for the following identity parameters for database assets:

Host system name

The name of the computer that hosts the database. If you are importing from a database, you can specify a different name than the name of the

source computer. For example, you might specify the computer that will host this database during development or production.

Database name

The name of the database that contains the imported schemas and tables. You can specify a different name than the name of the source database.

DBMS name

The name of the DBMS that hosts the database. The DBMS name is part of the identity of the target database. You can specify a different DBMS than the one that hosts the source database. The DBMS name should be appropriate for the value that you enter for database name.

DBMS server instance name

The name of the DBMS server instance, if it exists. Some database management systems do not have the concept of DBMS server instance. DBMS server instance name is part of the identity of the target database. You can specify a different DBMS server instance name than the one that hosts the source database. The DBMS server instance name should be appropriate for the value that you enter for database name.

Schema name

The name of the schema that the imported tables belong to.

Logical data model and physical data model assets

If you import a physical data model from a design tool, you can choose to create a database schema and database tables from the physical data model. This is necessary for InfoSphere DataStage and QualityStage users who want to create table definitions from these shared tables for use in jobs. You specify identity parameters for host system, database, and optionally DBMS to create a valid identity for the database schema. Both the physical data model and the database schema are stored in the metadata repository on import.

In the metadata repository, the identity of a logical data model or physical data model is a combination of the name of the model and a namespace value. You specify the value for the **Model namespace** parameter on the Identity Parameters screen when you import the model.

You can specify whatever value you want. The value does not have to correspond to an actual namespace structure. You can type a namespace value or browse to use an existing namespace value that is in the metadata repository.

By specifying a unique namespace value, you can distinguish between two different logical or physical models that have the same name. If you are importing logical and physical data models at the same time, the namespace value that you specify is used for each of them.

Important: In imports that are created by using design tool bridges in version 8.7 of InfoSphere Information Server, the identity of an imported logical or physical data model includes a namespace value that contains the path of the model file. If you imported the same data model with version 8.7, take either of the following actions:

- To merge the new data model with the previously imported data model, use the same value for **Model namespace** that was provided for you in the original import. You can copy this namespace value by browsing to the previously imported logical or physical data model and displaying the model on the **Repository Management** tab.

- To create a different identity for the current data model, specify a value for **Model namespace** that is different from the namespace value of the previously imported data model. The current data model is imported as a unique asset, while the previously imported model remains in the metadata repository. If desired, a Common Metadata Administrator can delete the previously imported data model on the **Repository Management** tab.

Chapter 5. Business intelligence assets

Business intelligence (BI) assets are used by BI tools to organize reports and models that provide a business view of data. These assets include BI reports, BI models, BI collections, and cubes.

You can use bridges to import BI assets from tools such as IBM Cognos and SAP BusinessObjects.

It is good practice when importing BI assets to simultaneously import the database tables that BI reports are based on. You can then use InfoSphere Information Governance Catalog to create data lineage reports that show the relationship between the database tables, the jobs that use the database tables, and the BI reports that are based on the tables.

You can use InfoSphere Metadata Asset Manager to browse and delete BI assets and manage duplicate BI assets.

Asset types

The following table lists and defines the types of BI assets that are stored in the metadata repository of InfoSphere Information Server.

Table 2. BI assets


Asset type	Definition	Components of the identity of the asset	Contained asset types
 BI server	<p>When a BI tool supports multiple servers on a single host computer, the BI server value is the name of the source tool server. When a BI tool supports a single server per host computer, the BI server value is the name or IP address of the host system.</p> <p>BI servers are displayed in InfoSphere Information Governance Catalog and on the Import tab of InfoSphere Metadata Asset Manager.</p>	<ul style="list-style-type: none">• BI server name	BI folder

Table 2. BI assets (continued)





Asset type	Definition	Components of the identity of the asset	Contained asset types
 BI folder	<p>The folder structure that contains BI models, or BI reports, or both in the source tool. BI folders can also contain other BI folders.</p> <p>BI folders are displayed in InfoSphere Information Governance Catalog and on the Import tab of InfoSphere Metadata Asset Manager.</p>	<ul style="list-style-type: none"> • BI folder name • Identity of the BI server, or, for subfolders, the identity of the containing BI folder 	BI folder, BI model, and BI report
 BI model	<p>A grouping of BI data collection views that are relevant to a BI application.</p>	<ul style="list-style-type: none"> • BI model name • Identity of BI folder 	Cube, BI collection, BI join, BI hierarchy, and BI filter
 BI collection	<p>A data structure that provides a view of data that is stored in databases and files. In dimensional modeling, these structures are known as dimensions and fact tables. BI collections are the data sources of BI reports.</p>	<ul style="list-style-type: none"> • BI collection name • BI collection namespace • Identity of the BI model that contains the collection, or, for subcollections, the identity of the BI collection that contains the subcollection 	BI collection member, BI level, BI hierarchy, and BI filter. BI collections can contain other BI collections.
 BI collection member	<p>The basic abstraction of a data value that is projected from a database column. BI collection members define the structure of the collection that owns them. There are two types of members: regular and measure. Regular members are dimension attributes that describe the characteristics and semantics of the owner collection. Measures represent analytic values that define a measurement entity in a fact collection.</p>	<ul style="list-style-type: none"> • BI collection member name • Identity of the BI collection 	

Table 2. BI assets (continued)













Asset type	Definition	Components of the identity of the asset	Contained asset types
 BI level	An asset that defines a logical step in the order of a BI hierarchy. A BI level consists of one or more BI collection members of the same BI collection that are related and function as a logical unit.	<ul style="list-style-type: none"> • BI level name • Identity of the BI collection 	BI level element
 BI level element	An associative class that assigns a BI collection member to a specific level within the collection.	<ul style="list-style-type: none"> • Identity of the BI collection member • Identity of the BI level 	
 Cube	A subset of a BI model that consists of a set of related analytic values that share the same dimensionality.	<ul style="list-style-type: none"> • Cube name • Cube namespace • Identity of the BI model 	Cube dimension and cube measure
 Cube dimension	An associative class that connects a cube to dimensions in the BI collection that are relevant to the analytic values of the cube. A cube dimension references the BI collection from which the dimension is derived and the relevant dimension hierarchy of the cube.	<ul style="list-style-type: none"> • Identity of the cube • Identity of the BI collection 	
 Cube measure	An associative class that connects a cube to BI collection members that are measures.	<ul style="list-style-type: none"> • Identity of the cube • Identity of the BI collection member 	
 BI filter	A filtering constraint on the source data that is viewed through a BI collection. Filters are either local or global. A local filter is owned by a single BI collection. A global filter is owned by the BI model and by one or more collections.	<ul style="list-style-type: none"> • BI filter name • BI filter namespace • Either the identity of the containing BI model or the containing BI collection 	

Table 2. BI assets (continued)

Asset type	Definition	Components of the identity of the asset	Contained asset types
 BI hierarchy	An organizational structure that defines an ordering or relationship of data within a BI collection.	<ul style="list-style-type: none"> • BI hierarchy name • BI hierarchy namespace • Either the identity of the containing BI model or the containing BI collection 	BI hierarchy member
 BI hierarchy member	An asset that orders BI levels within a hierarchy structure.	<ul style="list-style-type: none"> • Identity of the BI hierarchy • Identity of the BI level 	
 BI join	An asset that joins two database tables (a physical join) or two BI collections (a logical join). The physical join defines the data source of a BI collection and the logical join is used in a star schema between fact and dimension collections.	<ul style="list-style-type: none"> • BI join name • BI join condition • Identity of the BI model 	BI report query
 BI report	A business intelligence report that is based on information in a database or a BI model.	<ul style="list-style-type: none"> • BI report name • Identity of the BI folder 	BI report query
 BI report query	A query on a database or a BI model.	<ul style="list-style-type: none"> • BI report query name • BI report query namespace • Identity of the BI report 	BI report query item
 BI report query item	An asset that defines a column in a BI report query.	<ul style="list-style-type: none"> • BI report query item name • Identity of the BI report query 	

Appendix A. Product accessibility

You can get information about the accessibility status of IBM products.

The IBM InfoSphere Information Server product modules and user interfaces are not fully accessible.

For information about the accessibility status of IBM products, see the IBM product accessibility information at http://www.ibm.com/able/product_accessibility/index.html.

Accessible documentation

Accessible documentation for InfoSphere Information Server products is provided in an information center. The information center presents the documentation in XHTML 1.0 format, which is viewable in most web browsers. Because the information center uses XHTML, you can set display preferences in your browser. This also allows you to use screen readers and other assistive technologies to access the documentation.

The documentation that is in the information center is also provided in PDF files, which are not fully accessible.

IBM and accessibility

See the IBM Human Ability and Accessibility Center for more information about the commitment that IBM has to accessibility.

Appendix B. Contacting IBM

You can contact IBM for customer support, software services, product information, and general information. You also can provide feedback to IBM about products and documentation.

The following table lists resources for customer support, software services, training, and product and solutions information.

Table 3. IBM resources

Resource	Description and location
IBM Support Portal	You can customize support information by choosing the products and the topics that interest you at www.ibm.com/support/entry/portal/Software/Information_Management/InfoSphere_Information_Server
Software services	You can find information about software, IT, and business consulting services, on the solutions site at www.ibm.com/businesssolutions/
My IBM	You can manage links to IBM Web sites and information that meet your specific technical support needs by creating an account on the My IBM site at www.ibm.com/account/
Training and certification	You can learn about technical training and education services designed for individuals, companies, and public organizations to acquire, maintain, and optimize their IT skills at http://www.ibm.com/training
IBM representatives	You can contact an IBM representative to learn about solutions at www.ibm.com/connect/ibm/us/en/

Appendix C. Accessing the product documentation

Documentation is provided in a variety of formats: in the online IBM Knowledge Center, in an optional locally installed information center, and as PDF books. You can access the online or locally installed help directly from the product client interfaces.

IBM Knowledge Center is the best place to find the most up-to-date information for InfoSphere Information Server. IBM Knowledge Center contains help for most of the product interfaces, as well as complete documentation for all the product modules in the suite. You can open IBM Knowledge Center from the installed product or from a web browser.

Accessing IBM Knowledge Center

There are various ways to access the online documentation:

- Click the **Help** link in the upper right of the client interface.
- Press the F1 key. The F1 key typically opens the topic that describes the current context of the client interface.

Note: The F1 key does not work in web clients.

- Type the address in a web browser, for example, when you are not logged in to the product.

Enter the following address to access all versions of InfoSphere Information Server documentation:

```
http://www.ibm.com/support/knowledgecenter/SSZJPZ/
```

If you want to access a particular topic, specify the version number with the product identifier, the documentation plug-in name, and the topic path in the URL. For example, the URL for the 11.3 version of this topic is as follows. (The ⇒ symbol indicates a line continuation):

```
http://www.ibm.com/support/knowledgecenter/SSZJPZ_11.3.0/⇒  
com.ibm.swg.im.iis.common.doc/common/accessingiidoc.html
```

Tip:

The knowledge center has a short URL as well:

```
http://ibm.biz/knowctr
```

To specify a short URL to a specific product page, version, or topic, use a hash character (#) between the short URL and the product identifier. For example, the short URL to all the InfoSphere Information Server documentation is the following URL:

```
http://ibm.biz/knowctr#SSZJPZ/
```

And, the short URL to the topic above to create a slightly shorter URL is the following URL (The ⇒ symbol indicates a line continuation):

```
http://ibm.biz/knowctr#SSZJPZ_11.3.0/com.ibm.swg.im.iis.common.doc/⇒  
common/accessingiidoc.html
```

Changing help links to refer to locally installed documentation

IBM Knowledge Center contains the most up-to-date version of the documentation. However, you can install a local version of the documentation as an information center and configure your help links to point to it. A local information center is useful if your enterprise does not provide access to the internet.

Use the installation instructions that come with the information center installation package to install it on the computer of your choice. After you install and start the information center, you can use the **iisAdmin** command on the services tier computer to change the documentation location that the product F1 and help links refer to. (The `⇒` symbol indicates a line continuation):

Windows

```
IS_install_path\ASBServer\bin\iisAdmin.bat -set -key ⇒  
com.ibm.iis.infocenter.url -value http://<host>:<port>/help/topic/
```

AIX® Linux

```
IS_install_path/ASBServer/bin/iisAdmin.sh -set -key ⇒  
com.ibm.iis.infocenter.url -value http://<host>:<port>/help/topic/
```

Where `<host>` is the name of the computer where the information center is installed and `<port>` is the port number for the information center. The default port number is 8888. For example, on a computer named `server1.example.com` that uses the default port, the URL value would be `http://server1.example.com:8888/help/topic/`.

Obtaining PDF and hardcopy documentation

- The PDF file books are available online and can be accessed from this support document: <https://www.ibm.com/support/docview.wss?uid=swg27008803&wv=1>.
- You can also order IBM publications in hardcopy format online or through your local IBM representative. To order publications online, go to the IBM Publications Center at <http://www.ibm.com/e-business/linkweb/publications/servlet/pbi.wss>.

Notices and trademarks

This information was developed for products and services offered in the U.S.A. This material may be available from IBM in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

Notices

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785 U.S.A.

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing
Legal and Intellectual Property Law
IBM Japan Ltd.
19-21, Nihonbashi-Hakozakicho, Chuo-ku
Tokyo 103-8510, Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation
J46A/G4
555 Bailey Avenue
San Jose, CA 95141-1003 U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Each copy or any portion of these sample programs or any derivative work, must include a copyright notice as follows:

© (your company name) (year). Portions of this code are derived from IBM Corp. Sample Programs. © Copyright IBM Corp. _enter the year or years_. All rights reserved.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Privacy policy considerations

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session or persistent cookies. If a product or component is not listed, that product or component does not use cookies.

Table 4. Use of cookies by InfoSphere Information Server products and components

Product module	Component or feature	Type of cookie that is used	Collect this data	Purpose of data	Disabling the cookies
Any (part of InfoSphere Information Server installation)	InfoSphere Information Server web console	<ul style="list-style-type: none"> • Session • Persistent 	User name	<ul style="list-style-type: none"> • Session management • Authentication 	Cannot be disabled
Any (part of InfoSphere Information Server installation)	InfoSphere Metadata Asset Manager	<ul style="list-style-type: none"> • Session • Persistent 	No personally identifiable information	<ul style="list-style-type: none"> • Session management • Authentication • Enhanced user usability • Single sign-on configuration 	Cannot be disabled

Table 4. Use of cookies by InfoSphere Information Server products and components (continued)

Product module	Component or feature	Type of cookie that is used	Collect this data	Purpose of data	Disabling the cookies
InfoSphere DataStage	Big Data File stage	<ul style="list-style-type: none"> • Session • Persistent 	<ul style="list-style-type: none"> • User name • Digital signature • Session ID 	<ul style="list-style-type: none"> • Session management • Authentication • Single sign-on configuration 	Cannot be disabled
InfoSphere DataStage	XML stage	Session	Internal identifiers	<ul style="list-style-type: none"> • Session management • Authentication 	Cannot be disabled
InfoSphere DataStage	IBM InfoSphere DataStage and QualityStage Operations Console	Session	No personally identifiable information	<ul style="list-style-type: none"> • Session management • Authentication 	Cannot be disabled
InfoSphere Data Click	InfoSphere Information Server web console	<ul style="list-style-type: none"> • Session • Persistent 	User name	<ul style="list-style-type: none"> • Session management • Authentication 	Cannot be disabled
InfoSphere Data Quality Console		Session	No personally identifiable information	<ul style="list-style-type: none"> • Session management • Authentication • Single sign-on configuration 	Cannot be disabled
InfoSphere QualityStage Standardization Rules Designer	InfoSphere Information Server web console	<ul style="list-style-type: none"> • Session • Persistent 	User name	<ul style="list-style-type: none"> • Session management • Authentication 	Cannot be disabled
InfoSphere Information Governance Catalog		<ul style="list-style-type: none"> • Session • Persistent 	<ul style="list-style-type: none"> • User name • Internal identifiers • State of the tree 	<ul style="list-style-type: none"> • Session management • Authentication • Single sign-on configuration 	Cannot be disabled
InfoSphere Information Analyzer	Data Rules stage in the InfoSphere DataStage and QualityStage Designer client	Session	Session ID	Session management	Cannot be disabled

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at <http://www.ibm.com/privacy> and IBM's Online Privacy Statement at <http://www.ibm.com/privacy/details> the section entitled "Cookies, Web Beacons and Other Technologies" and the "IBM Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.

Trademarks

IBM, the IBM logo, and [ibm.com](http://www.ibm.com)[®] are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at www.ibm.com/legal/copytrade.shtml.

The following terms are trademarks or registered trademarks of other companies:

Adobe is a registered trademark of Adobe Systems Incorporated in the United States, and/or other countries.

Intel and Itanium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows and Windows NT are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java[™] and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

The United States Postal Service owns the following trademarks: CASS, CASS Certified, DPV, LACS^{Link}, ZIP, ZIP + 4, ZIP Code, Post Office, Postal Service, USPS and United States Postal Service. IBM Corporation is a non-exclusive DPV and LACS^{Link} licensee of the United States Postal Service.

Other company, product or service names may be trademarks or service marks of others.

Index

B

- BI assets 13
- BI metadata 1
- BI models 13
- BI reports 13
- bridge parameters
 - MicroStrategy bridge 5
- business intelligence assets 13
- business intelligence metadata 1

C

- cubes 13
- customer support
 - contacting 19

E

- express import 3

I

- identity parameters 9
- importing metadata 3
 - BI metadata 1
 - specifying identity values 9
- InfoSphere Metadata Asset Manager
 - importing assets 3

L

- legal notices 23

M

- managed import 3
- MicroStrategy bridge 5
 - upgrade requirements 8

P

- product accessibility
 - accessibility 17
- product documentation
 - accessing 21

S

- software services
 - contacting 19
- support
 - customer 19

T

- trademarks
 - list of 23

U

- upgrade requirements
 - MicroStrategy bridge 8



Printed in USA

SC19-4301-00

